



REVISION RECORD

REV	ECN#	DESCRIPTION	BY	DATE
A0			Shaey	2022-03-26

Table 1

Length	Tolerances
≤15m	+150 mm/-0 mm
>15m	+1%L mm/-0 mm



SECTION A-A / B-B

Type A

Side A Fiber Hole Position	Cable Fiber Color	Side B Fiber Hole Position
1	BLU	1
2	ORN	2
3	GRN	3
4	BRN	4
5	N/A	5
6	N/A	6
7	N/A	7
8	N/A	8
9	YEL	9
10	VIO	10
11	PNK	11
12	AQU	12

Type B

Side A Fiber Hole Position	Cable Fiber Color	Side B Fiber Hole Position
1	BLU	12
2	ORN	11
3	GRN	10
4	BRN	9
5	N/A	8
6	N/A	7
7	N/A	6
8	N/A	5
9	YEL	4
10	VIO	3
11	PNK	2
12	AQU	1

Table 2

TYPE	MPO/PC/SM/12F(STD)
	1310/1550nm
IL	≤0.60 dB
RL	>45 dB

TOLERANCE ON DECIMALS			PART NAME		DRAWING NO.		REV
X	±MM	±°	MPO PC(F)-MPO PC(F)-3.0mm-8F-SM-xxxM (Type A&B)				A0
X.X	±0.1	±0.1°	SCALE	QTY	PAGE	THIRD ANGLE PROJECTION	
X.XX	±0.05	±0.05°	UNIT	MATERIAL			
X.XXX	±0.005	±0.005°	mm	mm			
			DRAW	CHKD	APPROVED		