



Patch Cord Product Specification

Performance Specifications

Parameter		Value
Connector Type		FC/UPC,SC/UPC,LC/UPC FC/APC,SC/APC,LC/UPC
Wavelength (nm)		780
Insertion Loss (dB)		≤1.0
Return loss (dB)	UPC Type	≥50
	APC type	≥60
Extinction Ratio 23°C (dB)		≥20
Fiber Type		PM780 HP Fiber
Key Orientation		Slow Axis
Axis Alignment (deg)		±3
Durability		≤0.2
Operating temperature (°C)		-10~+70
Storage temperature (°C)		-40 ~ +80

Package

Antistatic bag: 21x24cm



Ordering information

PMJP	Wavelength	Pigtail Type	Fiber Length	Connector1	Connector2
	780nm	1=250um bare fiber	H=0.5m	0=None	0=None
			8=0.8m	1=FC/UPC	1=FC/UPC
		2=900um loose tube	1=1.0m	2=FC/APC	2=FC/APC
			5=1.5m	3=LC/UPC	3=LC/UPC
		3=3mm loose tube	2=2.0m	4=LC/APC	4=LC/APC
			3=3.0m	5=SC/APC	5=SC/APC
			4=4.0m	6=SC/UPC	6=SC/UPC
			A=2.5m		
			B=5.0m		