

EMCR16SLOT

2U 19" Rack-mount Chassis

Introduction

Rack-mounted chassis is a centralized and economical equipment of gather Ethernet media converter together. It covers two styles, 14 slots and 16 slots, mostly used in plant room with centralized dual power supply and automatic switch. Normal size is 2U, but 14 slots kind is for standalone device and 16 slots kind is for card style.

Features

- Main and vice power equipment ensure system work smoothly.
- Function cards supports hot-plugging and each card realizes its corresponding function independently.
- Double power panel slot supports two power supply units backup for each other.
- It would enhance the reliability of the rack.
- Supports 220V/110V AC switch mode power supply (SMPS) design.
- Power supply and other parameter state indicator LED can monitor the operation condition of system.
- Up to 14 or 16 available card type media converter module slots, 14 standalone media converter slots.
- With stable performance, large capacity of power supply, and easy for management and maintenance.
- All of the modules installed in the chassis are hot-swap, which makes it unnecessary to power-down the chassis when replacing modules.
- Support telecommunication operation requirement completely.

Technology Specification

- Structure : 2U Rack
- Ripple wave : $\leq 20\text{mv}$
- Power input : AC 85~265V 50/60HZ
- Power output : DC 5V 16A



深圳易天光通信有限公司

ETU-LINK TECHNOLOGY CO., LTD

- Power adapter: single power supply or dual power supply
- Power: 95W
- Operating Temperature : -10~55℃
- Operating Humidity : 5%~95%
- Storage Temperature : -40~70℃
- Storage Humidity : 5%~95% no condensing
- Dimension: 490mm x 230mm x 90mm for Rack

Pictures

2U 19"14 Slots Rack for Standalone Type MediaConverter



2U 19"14 Slots Rack for Standalone Type MediaConverter



2U 19"16 Slots Rack for Card Based Media Converter



2U 19"16 Slots Rack for Card Based MediaConverter



Order Information

Part Number	Description
EMCR16SLOT	16slot, 2U 19", Dual power supply, AC110V/220V